



Direct Drive Mini Aluminum Elevator

- **Industrial Duty Integrated with a New Ultra modern appeal**
- All Aluminum and Stainless Steel Construction
- Available in Multiple Drive configurations
 - Direct Drive with Stainless Motors
 - EBD Belt Drive
 - Flat Plate Drive
- Delrin Rollers
- Piling or Seawall Mount
- Standard Angle is 25° (Available in Various Angles including Vertical)

Options:

- Searmor Corrosion Resistant Winders for Long Lasting Durability
- Wireless Remote Control
- Limit Switch with Auto Stop
- Complete Disconnect Switch
- Aluminum Bunks or Wooden Bunks Included
- Self Adjusting Cable Keepers



⚡ Specifications ⚡

Size	Horse Power	Volt and Amperage	Cable Size and Length	Vertical Travel	Track Size	Max. Beam	Cradle Dimensions	Bunks	Pile Size
3,000 lb.	(1) 3/4 HP Stainless Steel*	120V/20A 240V/15A	5/16" x 16' Stainless Steel	12'	6" x 4" x 19' I-Beam	7' 6"	6' Dual Forks	3" x 8" x 8' Aluminum Bunks	10" Min. Driven
4,000 lb.	(1) 1 HP Stainless Steel*	120V/20A 240V/15A	5/16" x 16' Stainless Steel	12'	6" x 4" x 19' I-Beam	7' 6"	6' Dual Forks	3" x 8" x 8' Aluminum Bunks	10" Min. Driven

*Stainless Steel Motors are Standard on all Direct Drive and H2 High Speed Direct Drive Lifts Only