



Standard Direct Drive Aluminum Elevator

- All Aluminum and Stainless Steel Construction
- Low Draft Design
- Modern Compact Drive Units
- Solid Delrin Rollers
- All Stainless Steel Roller Pins
- Side Rollers (12k & Up)
- Standard Aluminum Bunks
- Stainless Steel Cables
- Heavy Duty Adjustable Guide Poles
- Piling or Seawall Mount
- Available in Various Angles including Vertical
- 10 Year Limited Warranty

Additional Options:

- SEArmor Corrosion Resistant Package for Long Lasting Durability
- Wireless Remote Control
- Auto Stop and Limit Switch
- Complete Disconnect Switch
- Stainless Steel Wash Down Motors
- Self Adjusting Cable Keepers



Specifications

***See our "Complete list of Other Accessories"

Size	Horse Power	Volt and Amperage	Cable Size and Length	Vertical Travel	Track Size	Max. Beam	Cradle Dimensions	Bunks	Pile Size
5,000 lb.	(2) 3/4 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 30' Stainless Steel	12'	6" x 4" x 25' I-Beam	8' 0"	7' Dual Forks	3" x 8" x 12' Aluminum Bunks	8" Min. Tied Back
7,000 lb.	(2) 3/4 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 30' Stainless Steel	12'	8" x 5" x 25' I-Beam	8' 0"	7' Dual Forks	3" x 8" x 12' Aluminum Bunks	8" Min. Tied Back
10,000 lb.	(2) 1 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 30' Stainless Steel	12'	8" x 5" x 25' I-Beam	9' 0"	8' Dual Forks	3" x 8" x 12' Aluminum Bunks	10" Min. Tied Back
12,000 lb.	(2) 1 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 42' Stainless Steel	11'	10" x 6" x 25' I-Beam	10' 0"	8' Dual Forks	3" x 10" x 14' Aluminum Bunks	10" Min. Tied Back
14,000 lb.	(2) 1 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 42' Stainless Steel	11'	10" x 6" x 25' I-Beam	10' 0"	8' Dual Forks	3" x 10" x 14' Aluminum Bunks	10" Min. Tied Back
15,000 lb.	(2) 1 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 42' Stainless Steel	11'	10" x 6" x 25' I-Beam	10' 0"	8' Dual Forks	3" x 10" x 14' Aluminum Bunks	10" Min. Tied Back
17,000 lb.	(2) 1 HP Stainless Steel*	240V/20A	5/16" x 56' Stainless Steel	11'	12" x 7" x 25' I-Beam	12' 0"	10' Dual Forks	3" x 10" x 14' Aluminum Bunks	12" Min. Tied Back
20,000 lb.	(2) 1 HP Stainless Steel*	240V/20A	5/16" x 56' Stainless Steel	11'	12" x 7" x 25' I-Beam	12' 6"	10' Dual Forks	3" x 10" x 14' Aluminum Bunks	12" Min. Tied Back

*Stainless Steel Motors are Standard on all Direct Drive and H2 High Speed Direct Drive Lifts Only